




| | |
|---|--------------------------------|
| Brick shape | CERTIFICATE - CE - 1372 |
|  | 11 |
| | 1372-CPD-1460 |
| | EN 771-1:2011+A1:2015 |

| TECHNICAL SPECIFICATIONS | |
|---|--|
| Category: | II ,LD, |
| Lightened clay brick (L04) | 100(mm) x 250(mm) x 250(mm) Brick for masonry |
| Dimensions: | width(100mm) \pm 1 height(250mm) \pm 2 length(250mm) \pm 2 |
| Weight per piece: | 3380 gr |
| STRUCTURAL SPECIFICATIONS | |
| Configuration: | According to the presented design (structural group) |
| Size of support mm²: | 24900 |
| Outer wall thickness mm: | \geq 8 |
| Inner wall thickness mm: | \geq 6 |
| Determinig voids %: | 75 \pm 2% |
| Piece per pallet/m³ | 160 |
| Compressive strength N/mm²: | average \geq 3.72 N/mm² (perpendicular to base) |
| Demolition charge kN: | \geq 93950 kN |
| Content of soluble active salts: | Don't have |
| Water absorption % : | \geq 14 |
| Gross dry density: | 540.8 kg/m ³ dhe 540.8 kg/pallet |
| Frost resistance: | Bricks are frost resistant |

“KID - ALB” sh.p.k, NIPT: K52128506K, web: www.kid-alb.com,

Adresa: Maminas, Durrës, Albania, Tel: + 355 69 40 50 773, Mob:+355 69 70 61 875