




Brick shape	CERTIFICATE - CE - 1372
	11
	1372-CPD-1460
	EN 771-1:2011+A1:2015

TECHNICAL SPECIFICATIONS	
Category:	II ,LD,
Termic clay brick (T01/3)	300(mm) x 250(mm) x 250(mm) Brick for masonry
Dimensions:	width(300mm) \pm 1 height(250mm) \pm 1 length(250mm) \pm 1
Weight per piece:	11800 gr
STRUCTURAL SPECIFICATIONS	
Configuration:	According to the presented design (structural group)
Size of support mm²:	75000
Outer wall thickness mm:	\geq 9
Inner wall thickness mm:	\geq 7
Determinig voids %:	72 \pm 2%
Termic conductivity (λ) w/m^{°K}	0.4546
Compressive strength N/mm²:	average \geq 2.99 N/mm² (perpendicular to base)
Demolition charge kN:	\geq 185471 kN
Content of soluble active salts:	Don't have
Water absorption % :	\geq 14
Gross dry density:	566.4 kg/m ³ dhe 634.8 kg/pallet
Frost resistance:	Bricks are frost resistant

“KID - ALB” sh.p.k, NIPT: K52128506K, web: www.kid-alb.com,

Adresa: Maminas, Durrës, Albania, Tel: + 355 69 40 50 773, Mob:+355 69 70 61 875