




Brick shape	CERTIFICATE - CE - 1372
	11
	1372-CPD-1460
	EN 771-1:2011+A1:2015

TECHNICAL SPECIFICATIONS	
Category:	II ,LD,
Termic clay brick (T01/2)	200(mm) x 250(mm) x 250(mm) Brick for masonry
Dimensions:	width(200mm) \pm 1 height(250mm) \pm 2 length(250mm) \pm 2
Weight per piece:	6,300 gr
STRUCTURAL SPECIFICATIONS	
Configuration:	According to the presented design (structural group)
Size of support mm²:	49,431
Outer wall thickkness mm:	\geq 8
Inner wall thickness mm:	\geq 6
Determinig voids %:	70 \pm 2%
Piece per pallet/m³	80
Compressive strength N/mm²:	average \geq 2.72 N/mm² (perpendicular to base)
Demolition charge N:	\geq 166,100 N
Content of soluble active salts:	Don't have
Water absorption % :	\geq 14
Gross dry density:	590 kg/m ³ dhe 504 kg/pallet
Frost resistance:	Bricks are frost resistant

“KID - ALB” sh.p.k, NIPT: K52128506K, web: www.kid-alb.com,

Adresa: Maminas, Durrës, Albania, Tel: + 355 69 40 50 773, Mob:+355 69 70 61 875